



Wrap-Around Style Safety Spectacle

KEY FEATURES

- › Integral lateral protection
- › 3-position length adjustment
- › Soft comfort ventilated nose pads
- › Soft temple ends
- › Interchangeable lens functionality
- › Lightweight: only 22g
- › Optical class 1 Polycarbonate lens



CLEAR



GREY

SUITABLE FOR

ITEM NO.	VERSIONS	LENS MARKING	FRAME MARKING	PROTECTION AGAINST	COATINGS
BME00004KZ	CLEAR	○	2C-1.2 ▶ 1FT CE	▶ EN 166 FT CE BM04	Impacts, UV radiations
BME00004RZ					Anti-scratch+anti-fog
BME00004FZ	GREY	●	5-2.5 ▶ 1FT CE	▶ EN 166 FT CE BM04	Impacts, UV and Sun Glare



GENERAL SPECIFICATIONS

LENS BASE	9.5mm
WEIGHT	22g

PACKAGING

Individually contained in a polythene bag with a Euroslot

PER BOX	10
PER CARTON	200

COMPONENT SPECIFICATION

COMPONENT	MATERIAL	FEATURES
LENS AND NOSEBRIDGE	Polycarbonate	
TEMPLE	Polycarbonate	Robust and durable
HINGE	Stainless steel	Hard wearing

LENS MARKINGS

LENS FILTER TYPE:

2C UV
5 Solar

SCALE NUMBER (SHADE):

1.2 Clear
2.5 Grey

► Identity of the manufacturer

OPTICAL CLASS:

1 High optical quality

MECHANICAL STRENGTH:

F Low energy impact, resists a 6mm, 0.86g ball at 45m/s
T Protection against high-speed particles at extreme temperatures

CE Certification mark

FRAME MARKINGS

► Identity of the manufacturer

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

MECHANICAL STRENGTH:

F Low energy impact, resists a 6mm, 0.86g ball at 45m/s
T Protection against high-speed particles at extreme temperatures
CE Certification mark

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfibre pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

EUROPE

www.globus.co.uk

E: sales@globus.co.uk

T: +44 (0)161 877 4747

F: +44 (0)161 877 4746

MIDDLE EAST AND AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com

T: +971 4 882 9962

F: +971 4 882 9963



Globus (Shetland) Ltd, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM
Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES

© 2019 Globus (Shetland) Ltd | BMK-DATA-BM04-0919_1

EC-Type certification issued by:

0530: CERTOTTICA SCARL, Zona Industriale Villanova, 32013 - Longarone (BL), Italy, 0194: INSPEC, 56 Leslie Hough Way, Salford, Greater Manchester, M6 6AJ, UK, 0321: SATRA, Windham Way, Telford Way, Kettering, NN16 8SD, UK, 1105: CCOQS UK Ltd, 5 Harbour Exchange Square, London, E14 9GE, UK, 0196: DIN CERTCO, Gesellschaft für Konformitätsbewertung mbH, Alboinstr. 56, D-12103, Berlin, 0403: FIOH, P.O. Box 40, FI-00032.

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.